



RL2-1000(2V1000Ah)

Specification

Cells Per Unit	1
Voltage Per Unit	2V
Nominal Capacity	1000Ah@10hour-rate to 1.80V per cell @25°C
Weight	Approx. 51.0 Kg (Tolerance $\pm 5.0\%$)
Internal Resistance	$\leq 0.48 \text{ m}\Omega$ (Full Charge Condition @25°C)
Terminal	Default F10(M8)
Max. Discharge Current	3200A (5 sec)
Short Circuit Current	6850A
Design Life	20 years
Max. Charging Current	200 A
Reference Capacity	C ₁ 550.0Ah C ₃ 750.0Ah C ₅ 850.0Ah C ₁₀ 1000.0Ah
Standby Use Voltage	2.27 V~2.30 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	2.43 V~2.47 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: -0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C $\pm 5^\circ\text{C}$
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging be stored for up to 6 months at 25°C and then recharging than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



RL series is a general purpose battery with 20 years design life in float service. It meets with heavy duty grids, thicker plates, special additives and advanced AGM valve regulated technology, the RL series battery provides consistent performance and long service life. The new grid design effectively reduces the internal resistance, which provides higher specific energy density and excellent high rate discharge characteristics. It is suitable for communications back-up power and EPS/UPS applications.



ISO 9001



ISO 14001



ISO 45001






MH 28539



BSTXD210316008515EC

Dimensions



F10 TERMINAL

Length	410 $\pm$ 2mm (16.1 inches)
Width	172 $\pm$ 2mm (6.77 inches)
Height	330 $\pm$ 2mm (13.0 inches)
Total Height	342 $\pm$ 2mm (13.5 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m

Unit: mm

Constant Current Discharge Characteristics : A (25°C)

F.V/Time	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR
1.60V	947.8	611.0	376.3	282.0	227.0	188.7	126.8	105.5
1.65V	909.9	590.0	364.3	273.3	220.9	183.8	125.4	104.2
1.70V	869.7	570.9	352.3	265.9	214.9	179.0	123.4	102.6
1.75V	831.3	550.0	339.9	258.0	209.4	174.5	121.7	101.3
1.80V	794.5	529.0	327.8	250.0	203.4	170.0	119.6	100.0
1.85V	684.3	474.4	300.3	231.1	189.0	158.5	112.3	94.1

Constant Power Discharge Characteristics : W/Cell (25°C)


F.V/Time	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR
1.60V	1721.5	1148.2	713.1	538.7	435.9	363.7	247.6	207.4
1.65V	1670.1	1115.2	693.7	524.3	425.7	355.5	245.4	205.1
1.70V	1612.3	1085.7	674.6	512.3	415.7	347.5	242.1	202.3
1.75V	1556.9	1052.3	654.0	499.1	406.6	339.9	239.2	199.9
1.80V	1503.1	1017.9	633.8	485.6	396.3	332.3	235.7	197.6
1.85V	1307.4	918.6	583.9	450.9	369.7	310.9	221.8	186.3

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values. The battery must be fully charged before the capacity test. The C₁₀ should reach 95% after the first cycle and 100% after the third cycle.


RL2-1000(2V1000Ah)




Discharge Characteristics Curve




Charge Characteristic Curve For Standby Use(IU)




Cycle Life In Relation To Depth Of Discharge




Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity




Storage Characteristics



Effect Of Temperature On Long Term Life



Charge Characteristic Curve For Standby Use



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.